# **AR-Line MC**

AR-Line MC

#### **Datasheet**

AR-Line MC linear luminaire series offer simple and stylish illumination on different architectural structures with wide color options. They provide homogeneous image with custom made diffuser.

Practical and simple architectural illumination can be achieved with this fixed color luminaire series. Airline MC family is designed to operate hassle-free for many years under harsh environmental conditions.



Control

External DMX512/RDM External DALI ON/OFF





## **General Specifications**

AR-Line MC

- With its aluminum extrusion body UV-resistant diffuser, it is designed to operate smoothly for many years under harsh environmental conditions.
- With IP67 protection class feature, they work flawlessly under harsh weather conditions.
- They provide visual harmony to architectural structures with body color options.
- Due to external DMX512 protocol support, it provides full compatibility with external control software such as Madrix 5, ENTTEC ELM.









## **Technical Specifications**

### AR-Line MC

#### General

Control External DMX512/RDM

Color Depth 256

### Physical

Size 1 17/32" x 1 9/64"

Body Aluminum Extrusion

Connections IP67 Connector

Working Temperature -13 °F ~ 122°F

Protection Class IP67

\* Product lengths may vary. For details, see the technical drawing section.

### Optical

Luminous Flux 1750lm\* Viewing Angle 120°

\* Lumen value is given when all LEDs are at full power.

#### Electrical


Power 10 ~ 20W\* Operating Voltage 24VDC

\* Power consumption may vary with product length and pixel structure.




## **Technical Drawing**

## AR-Line MC



## **Options**





## **Accessories**

## AR-Line MC

#### **Connection Accessories**





Extension cable

Input cable

### **Mounting Accessories**







U type mounting bracket



M4 Allen Key

